

FOR SPECIFICATION REFER TO VULCANITE.COM.AU

AS 1100.201-1992		
0 - 6	±0.1	
6 - 30	±0.2	
30 - 120	±0.3	
120 - 400	±0.5	
400 - 1000	±0.8	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON AL DIMENSION OF LENGTH AND ANGLE ON RUBBER ARE TO CLASS M3 OF STANDARD ISO 3302-I: 1996 AND ON METAL ARE TO AS 1100.201-1992 AND AS1365-1986

	ISO 3302-I: 1996 CLASS M3				
L	RANGE	SPEC	25 - 40	±0.60	MET
E D	0 - 6.3	±0.25	40 - 63	±0.80	
	6.3 - 10	±0.30	63 - 100	±1.00	FINIS
	10 - 16	±0.40	100 - 160	±1.30	WEIG
	16 - 25	±0.50	160 -	±0.8%	

	ELASTOMER SPEC: NATURAL RUBBER	ALL DIMENSIONS ARE IN MILLIMETRES WITH INCHES SHOWN INSIDE []		
)				
	METAL SPEC:		10T TO 0041 F	
)	250 GRADE NOT TO SCA		IOT TO SCALE	
		SI7F:		
)	MATT BLACK ENAMEL	0.22	THIRD ANGLE PROJECTION	
	TIMIT DENCIN LIMITEL	A 🔿		
)	WEIGHT:	A3		
6	3.9			

vulcanite



7 X 7 X 4 SMALL ELASTOMER

VP2402