



FOR SPECIFICATION
REFER TO
VULCANITE.COM.AU

AS 1100.20		
0 - 6	±0.1	UNLESS O
6 - 30	±0.2	DIMENSION TO CLASS
30 - 120	±0.3	ON M
120 - 400	±0.5	
400 - 1000	±0.8	

OTHERWISE SPECIFIED, TOLERANCE ON AL N OF LENGTH AND ANGLE ON RUBBER AR S M3 OF STANDARD ISO 3302-I: 1996 ANI METAL ARE TO AS 1100.201-1992 AND AS1365-1986

	ISO 3302-I: I996 CLASS M3				ELAST
LL	RANGE	SPEC	25 - 40	±0.60	METAL
RE ND	0 - 6.3	±0.25	40 - 63	±0.80	
	6.3 - 10	±0.30	63 - 100	±1.00	FINISH
	10 - 16	±0.40	100 - 160	±1.30	WEIGH
	16 - 25	±0.50	160 -	±0.8%	

ELASTOMER SPEC NATURAL RUBBER METAL SPEC.	ALL DIMENSIONS ARE IN MILLIMETRE WITH INCHES SHOWN INSIDE []	
K1045 STEEL	NOT TO SCALE	
FINISH RUST VETO	SIZE:	THIRD ANGLE PROJECTION
WEIGHT:	$\Delta \prec$	((;)) — —

1.46 [3.22 lbs]



98mm O.D. CYLINDRICAL BUSH

VP2880