



|   |                  |      |  |                           |       |           |       |  |  |   |   |   |                  |   |
|---|------------------|------|--|---------------------------|-------|-----------|-------|--|--|---|---|---|------------------|---|
| FOR SPECIFICATION<br>REFER TO<br>VULCANITE.COM.AU | AS 1100.201-1992 |      | UNLESS OTHERWISE SPECIFIED, TOLERANCE ON ALL<br>DIMENSION OF LENGTH AND ANGLE ON RUBBER ARE<br>TO CLASS M3 OF STANDARD ISO 3302-1: 1996 AND<br>ON METAL ARE TO AS 1100.201-1992 AND<br>AS1365-1986 | ISO 3302-1: 1996 CLASS M3 |       |           |       | ELASTOMER SPEC:<br>NATURAL RUBBER                            |  | ALL DIMENSIONS ARE IN MILLIMETRES<br>WITH INCHES SHOWN INSIDE □ |   | vulcanite<br>Excellence in engineered rubber solutions. |                  |  |
|   | 0 - 6            | ±0.1 |  | RANGE                     | SPEC  | 25 - 40   | ±0.60 | METAL SPEC:<br>250 GRADE MILD STEEL                          |  | NOT TO SCALE  |   | TITLE:<br>CHEVRON SPRING                                | DWG No<br>VP3489 |   |
|   | 6 - 30           | ±0.2 |  | 0 - 6.3                   | ±0.25 | 40 - 63   | ±0.80 | FINISH:<br>MATT BLACK ENAMEL<br><br>WEIGHT:<br>9.1 [20.1 LB] |  | SIZE:<br>A3   | THIRD ANGLE PROJECTION<br> |   |                  |   |
|   | 30 - 120         | ±0.3 |  | 6.3 - 10                  | ±0.30 | 63 - 100  | ±1.00 |  |  |   |   |   |                  |   |
|   | 120 - 400        | ±0.5 |  | 10 - 16                   | ±0.40 | 100 - 160 | ±1.30 |  |  |   |   |   |                  |   |
|   | 400 - 1000       | ±0.8 |  | 16 - 25                   | ±0.50 | 160 -     | ±0.8% |  |  |   |   |   |                  |   |